



WPL Diamond DMC

Loadings:

Model	DMC 6	DMC 7	DMC 8	DMC 9
Population range (persons)	21-27	28-35	36-45	46-55
Blower motor size (kw)* single phase rating	0.0230	0.221	0.221	0.221
Total power consumption	0.460	0.663	0.663	0.663

*Actual power consumption may vary (dependent on motor efficiency and nature of installation), size stated is the motor size NOT actual power consumption. Additional Blower options are available on request. Loadings are based on British Water Code of Practice Flows and Loads 4 (on sizing criteria, treatment capacity for small wastewater treatment systems).

Dimensions:

Model	Max outside diameter (m)	Height to inlet (m)	*Inlet invert depth (mm)	**Height to outlet (m)	Outlet invert depth (mm)	Max height/in ground depth (m)	Weight empty (kg)	Total capacity (ltr)
DMC 6	3.30	2.78	570	2.68	665	3.35	380	9056
DMC 7	3.30	2.78	570	2.68	665	3.35	380	9056
DMC 8	3.30	3.14	580	3.04	680	3.72	460	15038
DMC 9	3.30	3.14	580	3.04	680	3.72	460	15038

*Deeper inverts can be accommodated with our range of standard invert extensions.

**Diamond units equipped with an EPC have 32mm MDPE pipe outlet and the outlet invert depth is 300mm for all models.

For more information, please visit: www.wplltd.com.